

Liebherr LHM 280

Specifications

The crane is slightly smaller and more slender than the two "big" cranes, and it is more mobile.

The crane has a capacity of 80 tonnes by the hook (+10 % at slow speed).

Egenvægt af krogblok: 2,2 t

Egenvægt af container åg (spreader): 9,0 t

SWL åg (spreader): 41,0 t

Radius (m)	Krogdrift	Krogdrift 110%	Under åg (spreader)
	Under krog	Under krog	
10	81,8	90,0	41,0
11	81,8	90,0	41,0
12	81,8	90,0	41,0
13	81,8	90,0	41,0
14	81,8	90,0	41,0
15	81,8	90,0	41,0
16	79,6	87,6	41,0
17	74,3	81,7	41,0
18	70,6	77,7	41,0
19	66,1	72,7	41,0
20	62,9	69,2	41,0
21	60,0	66,0	41,0
22	56,4	62,0	41,0
23	52,8	58,1	41,0
24	49,2	54,1	40,2
25	46,3	50,9	37,3
26	43,4	47,7	34,4
27	41,0	45,1	32,0
28	38,5	42,4	29,5
29	36,5	40,2	27,5
30	34,4	37,8	25,4
31	32,7	36,0	23,7
32	30,9	34,0	21,9
33	29,4	32,3	20,4
34	27,9	30,7	18,9
35	26,6	29,3	17,6
36	25,2	27,7	16,2
37	24,1	26,5	15,1
38	22,9	25,2	13,9
39	21,7	23,9	12,7
40	20,4	22,4	11,4

* Kranbevægelse er stoppet ikke på 100 % men på 110%
Alle værdier er i tons.